

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (rpm)		Weight
	尺寸				额定负荷极限		极限转速		重量
轴承型号	d	D	B	r _{s min}	Dynamic (Cr)	Static (Cor)	Grease	Oil	Kg
					动载	静载	脂	油	
24024	120	180	60	2	390	670	1,500	2,300	5.48
24024K30	120	180	60	2	390	670	1,500	2,300	5.39
24024K30W33C3	120	180	60	2	390	670	1,500	2,300	5.39
24024W33C3	120	180	60	2	390	670	1,500	2,300	5.48
24026	130	200	69	2	505	895	1,300	2,100	8.08
24026K30	130	200	69	2	505	895	1,300	2,100	7.95
24026K30W33C3	130	200	69	2	505	895	1,300	2,100	7.95
24026W33C3	130	200	69	2	505	895	1,300	2,100	8.08
24028	140	210	69	2	510	945	1,200	1,900	8.57
24028K30	140	210	69	2	510	945	1,200	1,900	8.43
24028K30W33C3	140	210	69	2	510	945	1,200	1,900	8.43
24028W33C3	140	210	69	2	510	945	1,200	1,900	8.57
24030	150	225	75	2.1	585	1,060	1,200	1,800	10.7
24030K30	150	225	75	2.1	585	1,060	1,200	1,800	10.5
24030K30W33C3	150	225	75	2.1	585	1,060	1,200	1,800	10.5
24030W33C3	150	225	75	2.1	585	1,060	1,200	1,800	10.7
24032	160	240	80	2.1	650	1,200	1,100	1,700	13
24032K30	160	240	80	2.1	650	1,200	1,100	1,700	12.8
24032K30W33C3	160	240	80	2.1	650	1,200	1,100	1,700	12.8
24032W33C3	160	240	80	2.1	650	1,200	1,100	1,700	13
24034	170	260	90	2.1	800	1,470	1,000	1,600	17.7
24034K30	170	260	90	2.1	800	1,470	1,000	1,600	17.4
24034K30W33C3	170	260	90	2.1	800	1,470	1,000	1,600	17.4
24034W33C3	170	260	90	2.1	800	1,470	1,000	1,600	17.7
24036	180	280	100	2.1	965	1,770	950	1,500	23.3
24036K30	180	280	100	2.1	965	1,770	950	1,500	22.9
24036K30W33C3	180	280	100	2.1	965	1,770	950	1,500	22.9
24036W33C3	180	280	100	2.1	965	1,770	950	1,500	23.3
24038	190	290	100	2.1	995	1,850	900	1,400	24.3
24038K30	190	290	100	2.1	995	1,850	900	1,400	23.9
24038K30W33C3	190	290	100	2.1	995	1,850	900	1,400	23.9
24038W33C3	190	290	100	2.1	995	1,850	900	1,400	24.3
24040	200	310	109	2.1	1,160	2,140	850	1,300	31
24040K30	200	310	109	2.1	1,160	2,140	850	1,300	30.5
24040K30W33C3	200	310	109	2.1	1,160	2,140	850	1,300	30.5

24040W33C3	200	310	109	2.1	1,160	2,140	850	1,300	31
24044	220	340	118	3	1,350	2,570	770	1,200	40.2
24044K30	220	340	118	3	1,350	2,570	770	1,200	39.6
24044K30W33C3	220	340	118	3	1,350	2,570	770	1,200	39.6
24044W33C3	220	340	118	3	1,350	2,570	770	1,200	40.2
24048	240	360	118	3	1,410	2,770	700	1,100	43
24048K30	240	360	118	3	1,410	2,770	700	1,100	42.3
24048K30W33C3	240	360	118	3	1,410	2,770	700	1,100	42.3
24048W33C3	240	360	118	3	1,410	2,770	700	1,100	43
24052	260	400	140	4	1,830	3,550	640	980	65.2
24052K30	260	400	140	4	1,830	3,550	640	980	64.1
24052K30W33C3	260	400	140	4	1,830	3,550	640	980	64.1
24052W33C3	260	400	140	4	1,830	3,550	640	980	65.2
24056	280	420	140	4	1,950	3,950	590	900	69
24056K30	280	420	140	4	1,950	3,950	590	900	67.9
24056K30W33C3	280	420	140	4	1,950	3,950	590	900	67.9
24056W33C3	280	420	140	4	1,950	3,950	590	900	69
24060	300	460	160	4	2,450	4,950	540	840	98
24060K30	300	460	160	4	2,450	4,950	540	840	96.4
24060K30W33C3	300	460	160	4	2,450	4,950	540	840	96.4
24060W33C3	300	460	160	4	2,450	4,950	540	840	98